# **FALL PROTECTION**

### **POINTGUARD**<sup>TM</sup> ANCHORAGE STRAPS

- Durable polyester webbing is economical, quick and easy to install
- When anchorage connector is no longer needed, simply cut strap and throw away
- · Available in two models:
  - Residential construction (3' length)
  - Concrete construction (4' length, includes protective sheath)
- 400-lb. (182 kg) capacity



## MSA

Model	Mfg.		Anchorage		Price
No.	No.	Type	Connector	Length'	/Each
SAM476	10042792	Residential	D-Ring	3	
SAM477	10042793	Residential	Web Loop	3	
SAM478	10042794	Concrete	D-Ring	4	
SAM479	10042795	Concrete	Web Loop	4	

#### FP STRYDER BEAM ANCHORS

- Easy, single hand installation
- Lightweight 4.5 lbs. unit
- Low friction wear pads with Teflon allows the anchor to glide effortlessly along the beam flange
- Integral load indicator alerts the user if the unit has been exposed to a fall
- Versatile design allows for mounting overhead or at worker's feet
- Easy to use, push-button adjustment with 1/4" adjustment intervals
- Fits beam flange widths from 14" to 23.5"
- 400-lb work capacity





Model	Mfg.	Fits	Price
No.	No.	Beams"	/Each
SA0684	10051961XL	14 to 23.5	

#### **BOSUN CHAIRS**

- Best method to sit suspended for long durations
- Padded seat ensures comfort during use
- Adjustable web assembly ensures security
- Designed to be used in conjunction with full body harnesses
- Bosun chair, attached to D-ring, will keep the user in upright position
- 5" x 16 1/2" padded seat, black nylon straps, 2 carabiners

Order No. SAM399 Mfg. No. SSH3505017



#### **ANCHORAGE STRAPS** • D-ring on one end and a

- sewn loop on the other end
- Length: 5'



### MSA

Model No.	Mfg. No.	Material	Price/Each
SAM474	505282	Nylon	
SAM475	505298	Polyester	

#### **D-PLATE ANCHORAGE CONNECTORS**

- · Provides permanent anchorage point
- · Bolts to beams or columns



SAM483

## MSA

Model No.	Mfg. No.	Material	Price /Each
SAM483	506632	Zinc-Plated Steel	
SAM484	506672	Anodized Aluminum Back-Plate	

#### **CARABINERS**

ALL CARABINERS HAVE A MINIMUM **BREAKING STRENGTH OF 5000 LBS.** 





- 2" (50 mm) gate opening
- Auto-locking
- Steel

Order No. SAM502 Mfg. No. 506308



- · 2.1" (52 mm) gate opening
  - Auto-locking
  - Steel

Order No. SAM503 Mfg. No. SRCC734G



- 7/8" (22 mm) gate opening
- Auto-locking Aluminum
- Order No. SAM499 Mfg. No. 506259



- 1" (25 mm)
- gate opening Auto-locking
- Steel

Order No. SAM500 Mfg. No. SRCC643



- 1.2" (32 mm) gate opening
- Auto-locking
- Steel

Order No. SAM501 Mfg. No. SRCC642





